



Prisma

STORAGE

250 kW Power Conversion System (PCS)

Prisma Storage is a modular power conversion system (PCS) designed to help you control and optimize your stored energy.

It is available as a standard pre-assembled cabinet (Power Conversion System, PCS) or as a Power Conversion Kit (PCK) for custom integration. This flexibility allows you to either deploy a ready-to-use solution or tailor the system to your specific installation needs.

Why energy storage?

- Maximize self-consumption from renewables
- Shift loads and avoid peak demand charges
- Stabilize power supply in weak-grid or remote areas
- Access energy markets for new revenue streams
- Reduce energy costs and increase resilience

Key advantages

- Pre-assembled PCS or customizable PCK
- Compatible with all storage types: batteries, fuel cells, supercapacitors,...
- Compact design for easy installation
- Single-phase, three-phase or mixed setup flexibility
- High efficiency for better battery management and longer lifespan
- Embedded supervision with Inview monitoring
- Scalable to match your growing energy needs

Compatible Modular Power Converters

Each Prisma Storage system can integrate up to six hot-swappable bidirectional modular power converters (MPC). The compatible module for this system is the PrismaBox 400 – 1DC/1AC – 750/400.



PrismaBox 400 – 1DC/1AC – 750/400.

AC1 In/Out Voltage (range)	3x400 Vac or 3x480Vac (260-537Vac)
DC2 In/Out Voltage (range)	750 Vdc (300-900 Vdc)
Power	42,5kW or 50kW
Form Factor	2RU, 27kg



Technical characteristics

Mechanical & Environmental Specifications	
Part Number	A00055-V01
Dimensions (W x H x D)	600x800x2100 mm
Total weight	+/- 370 Kg
Ingress Protection	IP20
Cooling type	Fan forced cooling
RoHS / Material (casing)	Compliant / Sheet Steel Powder Coated
Operating T° / Relative Humidity (RH) non-condensing	-20°C to 40°C, power de-rating from 40°C to 65°C / Max RH 95% for 96 hours per year
Storage T° / Relative Humidity (RH) non-condensing	-40°C to 70°C / Max RH 95%
Terminal type and size	RB012 - 185mm²
Maintenance access	All replaceable part accessible from the front
General Electrical Specifications (system-level electrical performance)	
Total Power	250kW
Number of power converters	Up to 6 PrismaBox
Monitoring & Control	7 inches touchscreen Inview X+
Peak efficiency (AC-DC or DC-AC)	> 98.5% at 50% load & nominal voltage
Overload capacity	150% for 15 seconds
Configuration / Neutral	Three Phase DELTA or STAR / TN-S, TN-C, TT
AC 1 In/Out	
Nominal voltage (Power)	3x400 -3x480VAC (250kW)
Voltage range (Line-Line)	3x260 Vac to 3x537 VAC (derating 3x260 to 355Vac)
Power factor / THDi	> 0.99 / < 3%
Frequency (Synchronization range)	50Hz or 60Hz (45 to 65Hz)
AC output voltage stability (Inverter mode)	±1% from 10% to 100% load
Static / Dynamic voltage regulation (Inverter mode)	±1% between 10% and 100% load / <5% from 0 to 100% to 0 load impact (100 ms)
DC 2 In/Out	
Nominal voltage (Power)	750VDC (250kW)
Voltage range	300 – 900VDC (power derating between 300 to 660VDC)
Reverse polarity protection	Yes
Standard compliance	
Electrical safety standard	IEC 62477-1, IEC 62109-1, IEC 62109-2, UL1741
EMC/EMI	IEC61000-6-X/ FCC Part 15 classA / IEC61000-4-X
Grid-Code	EN50549 VDE-AR-4105 AS4777 UL1741-SB IEEE1547
Low voltage switch gear & control gear assemblies	IEC61439-2
Integrated Protections (optional)	
AC side	Motorized MCCB 400A
DC side	Contacteur + Fuse 400A NH3-1000V
DC Earth leakage protection	Bender MRCDB423-D-1
Anti-islanding decoupling relay	Included ZHIEL UFR1001-E

Specifications can change without notice. New data will be updated on our website: www.cet-power.com. The present equipment is protected by several international patents, trademarks and copyrights.